

CARAVAN & BOAT MOVER

The world's No. 1 remote control caravan and boat mover.

CT2500-TAM

For dual or single axle caravans, boats etc. weighing up to 2500 kg.

RRP \$ **3,900**



Both the Camper-Trolley CT2500-TAM and the CT1500 ensure hassle-free, safe manoeuvring and positioning of your caravan, boat, or trailer into tight spaces. Both models are supplied with an attachment bracket. Simply attach the bracket, connect your Camper-Trolley, and using your handheld remote control, start positioning effortlessly your caravan or boat.

Camper-Trolleys require no after sales installation, and dispense with the need for tools or electrical wiring. They also negate the use of your jockey wheel, eliminating the possibility of damage to your drawbar and/or jockey wheel.

Camper-Trolleys can operate on a variety of surfaces (surface must be firm) thanks to its two heavy duty rubber tracks driven by planetary geared motors which are powered by a rechargeable lithium-ion battery. The Camper-Trolley moves at 9 meters per minute.

Camper-Trolley is a revolutionary hi-tech product manufactured according to the most modern design principles combined with cutting edge technology.

WORLD'S NO. 1 CARAVAN & BOAT MOVER



CT1500

For single axle caravans, boats etc. weighing up to 1700 kg.

RRP \$ **2,695**



For all information and retail outlets go to www.camperrolley.com.au

Technical Specifications



CT2500-TAM



CT1500

TRANSMITTING FREQUENCY

2.4 GHZ 

2.4 GHZ 

SPEED

9 metres per minute

9 metres per minute.

BATTERY CAPACITY

14.4 Volt, 6000 mAh Lithium Ion

14.4 Volt, 6000 mAh Lithium Ion

OPERATING CAPACITY

Approx. 40 min.

Approx. 30 min.

MOTOR

4 pce. 14.4 V planet gear motors

2 pce. 14.4 V planet gear motors

BATTERY CHARGER

240 V – 14.4 V, 1000 mAh.

240 V – 14.4 V, 1000 mAh.

WEIGHT

34 kg

18 kg

HAULAGE CAPACITY

Suitable for caravans and boats up to 2500 kg.

Suitable for caravans and boats up to 1700 kg.

VERTICAL/DOWNWARD PRESSURE

300 kg

300 kg

SAFETY

Built-in 3-minute safety shut-off function

Built-in 3-minute safety shut-off function

DIMENSIONS

54 cm (L) x 45.5 cm (W) x 29.5 cm (H)

39 cm (L) x 44 cm (W) x 28 cm (H)

WORKING SURFACE

Concrete, asphalt, paving, compacted gravel, dirt and grass.

DEALER

